

DATASHEET GRYPHON





GENERAL

Art.Nr:	G-1172-S/M
GTIN:	8057733308950
E-class number:	40-02-01-02
Customs tariff number:	63079098

Standards:	EN 358:2018,EN 361: 2002,EN 813:2008
Net weight:	2.80 kg
Gross weight:	2.80 kg



DATASHEET GRYPHON

Comfortable and ergonomic harness equipped with six attachment points and specifically developed for rope access work.

Main features:

• close-fitting construction and wide lumbar support belt with breathable

mesh padding for optimal comfort during prolonged suspensions;

• contoured shoulder straps with shape optimized to avoid neck chafing;

shoulder strap equipped with quick-release buckle;

• leg-loop quick-release buckles with indicator for correct insertion;

· leg-loops designed with targeted panel construction to ensure optimal

comfort while in suspension by relieving pressure in the groin area;

• adjustable rear straps that allow the leg loops to be moved along the legs;

• large EN 361 sternal attachment point to facilitate rescue operations;

• EN 358 lateral attachment points with two positions: outward-facing when in

use (work mode); inward-folded when not in use (stand-by mode) in order not to hamper the operator's movements;

• EN 361 dorsal attachment point designed to avoid accidentally getting

snagged, especially while working in confined spaces;

• attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;

• dedicated loop for quick-link, to be used for the addition of a ventral

rope clamp in combination with appropriate straps;

• two horizontal straps positioned on the shoulder straps and exclusively

intended for the insertion of HOOK REST support;

two dedicated loops for the connection of a

FEATURES

Attachment points:	Sternal aluminium attachment point, Dorsal steel attachment point, Side aluminium attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 7 kg:	0
Number of material loops 10 kg:	4
Number of material loops 15 kg:	0
Application areas:	Arborists, RBA rigging, Emergency, Facades cleaning, Rescue, Roofers, Route construction, Steelwork, Shaft, Telco energy, Wind energy, Working in confined spaces
Colour:	Black, Orange
Harness features:	Lanyard parking ring
Hand wash:	40 °C
Maximum body hight:	185 cm
Maximum lifetime:	10 years
Maximum hip size:	80 cm
Maximum leg size:	55 cm
Maximum temperature:	60 °C
Minimum body hight:	160 cm
Minimum hip size:	60 cm



DATASHEET GRYPHON

work-positioning seat; • four large gear-loops, six loops for the toolholder pouch and four slots for carrying-tools carabiners; • maximum load: 140 kg.

Minimum leg size:	45 cm
Minimum temperature:	-20 °C
Padding:	Shoulder paddings, Back padding, Leg paddings
Buckles:	stick_buckle, click_buckle
Adjusting buckles:	Adjusting buckles shoulders, Adjusting buckles hips, Adjusting buckles legs
DIMENSIONS	
Size:	S-M
MATERIAL	
Material:	Polyamide, Polyester, Polyethylene, Steel, Aluminium

www.skylotec.com I Datenblatt, 10.07.24