

# DATASHEET

# **GRYPHON**





### **GENERAL**

Art.Nr:	G-1172-M/L
GTIN:	8057733308967
E-class number:	40-02-01-02
Customs tariff number:	63079098

Standards:	EN 358:2018,EN 361: 2002,EN 813:2008
Net weight:	2.84 kg
Gross weight:	2.84 kg



## DATASHEET

## **GRYPHON**

Comfortable and ergonomic harness equipped with six attachment points and specifically developed for rope access work.

#### Main features:

 close-fitting construction and wide lumbar support belt with breathable mesh padding for optimal comfort during prolonged suspensions;

contoured shoulder straps with shape optimized to avoid neck chafing;

• shoulder strap equipped with quick-release buckle;

 leg-loop quick-release buckles with indicator for correct insertion;

• leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;

• adjustable rear straps that allow the leg loops to be moved along the legs;

• large EN 361 sternal attachment point to facilitate rescue operations;

• EN 358 lateral attachment points with two positions: outward-facing when in use (work mode); inward-folded when not in use (stand-by mode) in order not to hamper the operator's movements;

 EN 361 dorsal attachment point designed to avoid accidentally getting snagged, especially while working in confined spaces;

 attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;

 dedicated loop for quick-link, to be used for the addition of a ventral rope clamp in combination with appropriate

straps;

 two horizontal straps positioned on the shoulder straps and exclusively intended for the insertion of HOOK REST support;

two dedicated loops for the connection of a

#### **FEATURES**

Attachment points:	Sternal aluminium attachment point, Dorsal steel attachment point, Side aluminium attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 7 kg:	0
Number of material loops 10 kg:	4
Number of material loops 15 kg:	0
Application areas:	Arborists, RBA rigging, Emergency, Facades cleaning, Rescue, Roofers, Route construction, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Colour:	Black, Orange
Harness features:	Lanyard parking ring
Hand wash:	40 °C
Maximum body hight:	190 cm
Maximum lifetime:	10 years
Maximum hip size:	100 cm
Maximum leg size:	60 cm
Maximum temperature:	60 °C
Minimum body hight:	170 cm
Minimum hip size:	70 cm



## DATASHEET

# **GRYPHON**

work-positioning seat;
• four large gear-loops, six loops for the tool-holder pouch and four slots for carrying-tools carabiners;
• maximum load: 140 kg.

DIMENSIONS	
Adjusting buckles:	Adjusting buckles shoulders, Adjusting buckles hips, Adjusting buckles legs
Buckles:	stick_buckle, click_buckle
Padding:	Shoulder paddings, Back padding, Leg paddings
Minimum temperature:	-20 °C
Minimum leg size:	50 cm

#### DIMENSIONS

M-L Size:

#### **MATERIAL**

Polyamide, Polyester, Polyethylene, Steel, Material:

Aluminium