

## DATASHEET

# **GRYPHON ASCENDER**





### **GENERAL**

Art.Nr:	G-1176-M/L
GTIN:	8057733308998
E-class number:	40-02-01-02
Customs tariff	63079098

Standards:	EN 358:2018,EN 361: 2002,EN 813:2008
Net weight:	2.29 kg
Gross weight:	2.29 kg



### DATASHEET

## **GRYPHON ASCENDER**

Comfortable and ergonomic harness with six attachment points specifically developed for rope access work and equipped with a triangular quick-link and with CHEST ASCENDER+ ventral rope clamp, for maximum ease of use in rope manoeuvres.

#### Main features:

 close-fitting construction and wide lumbar support belt with breathable mesh padding for optimal comfort during prolonged suspensions:

contoured shoulder straps with shape optimized to avoid neck chafing;

optimized to avoid neck chailing;

• shoulder strap equipped with quick-release buckle;

• leg-loop quick-release buckles with indicator for correct insertion;

 leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area:

pressure in the groin area;

• adjustable rear straps that allow the leg

loops to be moved along the legs;

• large EN 361 sternal attachment point to facilitate rescue operations;

• EN 358 lateral attachment points with two positions: outward-facing when in use (work mode); inward-folded when not in use (stand-by mode) in order not to hamper the operator's movements;

 EN 361 dorsal attachment point designed to avoid accidentally getting snagged, especially while working in

confined spaces;

• attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;

 dedicated loop for quick-link, to be used for the addition of a ventral

rope clamp in combination with appropriate straps;

two horizontal straps positioned on the

#### **FEATURES**

Attachment points:	Sternal aluminium attachment point, Dorsal steel attachment point, Side aluminium attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 10 kg:	4
Application areas:	Arborists, RBA rigging, Emergency, Rescue
Colour:	Black, Orange
Harness features:	Lanyard parking ring, Integrated chest ascender
Hand wash:	40 °C
Maximum body hight:	190 cm
Maximum lifetime:	10 years
Maximum hip size:	100 cm
Maximum leg size:	60 cm
Maximum temperature:	60 °C
Minimum body hight:	170 cm
Minimum hip size:	70 cm
Minimum leg size:	50 cm
Minimum temperature:	-20 °C
Padding:	Back padding, Leg paddings, Shoulder paddings
Buckles:	stick_buckle, click_buckle



## DATASHEET

## **GRYPHON ASCENDER**

shoulder straps and exclusively intended for the insertion of HOOK REST support;

• two dedicated loops for the connection of a work-positioning seat;

• four large gear-loops, six loops for the toolholder pouch and four slots for carrying-tools carabiners;

· maximum load: 140 kg.

Adjusting buckles:	Adjusting buckles shoulders, Adjusting buckles hips, Adjusting buckles legs
DIMENSIONS	
Size:	M-L
MATERIAL	
Material:	Polyamide, Polyester, Polyethylene, Steel,

Aluminium