


Professional pocket scale

	<table border="1"> <thead> <tr> <th>Feature</th> </tr> </thead> <tbody> <tr> <td>• Robust design</td> </tr> <tr> <td>• Easy to use</td> </tr> <tr> <td>• LCD display, backlit</td> </tr> <tr> <td>• Auto-off function</td> </tr> <tr> <td>• Overload indication</td> </tr> <tr> <td>• Unit changeable (g, dwt, gn, ct)</td> </tr> <tr> <td>• Ready to use with 2xAAA batteries (included)</td> </tr> <tr> <td>• Can be calibrated by user</td> </tr> </tbody> </table>	Feature	• Robust design	• Easy to use	• LCD display, backlit	• Auto-off function	• Overload indication	• Unit changeable (g, dwt, gn, ct)	• Ready to use with 2xAAA batteries (included)	• Can be calibrated by user
Feature										
• Robust design										
• Easy to use										
• LCD display, backlit										
• Auto-off function										
• Overload indication										
• Unit changeable (g, dwt, gn, ct)										
• Ready to use with 2xAAA batteries (included)										
• Can be calibrated by user										

Models			
Item No.	Capacity	Division	Official calibration
MS500	500g	0.1g	Not legal for trade
MS1000	1000g	0.2g	Not legal for trade

Design	
Material housing	ABS plastic
Color	Silver
Outer measurements	128x77x19mm
Weighing platform	77x66mm
Net weight / gross weight	142g / 170g

Technical data	
Display	LCD, 31x11mm
Weighing units	Gram, Pennyweight, Grain, carat
Calibration	Can be calibrated by user
Conformity	CE, RoHS
Power supply	2xAAA batteries (included)
Operating temperature	10° - 30°C / 50° - 86°F
Data interface	Non
Manual	German, French, English
Scope of delivery	2xAAA batteries