

Cable cutter**Cable cutter**

- Easy handling
- Minimal hand force required
- Release option in every cutting position
- Not suitable for steel wires, steel-armoured cables, aluminium alloys and hard-drawn copper conductors!
- Do not cut at live conductors

KT 80

Cu + Al: max. 80 mm

Cu: max. 630 mm²
Al: max. 1.000 mm²

Cu: max. 630 mm²

**Technical data****Max. cutting performance, copper cable**

Copper cable - stranded, max.

Copper cable - flexible, max.

Copper sector cable

Max. cutting performance, aluminium cable

Stranded aluminium cable, max (mm²)

Stranded aluminium cable, max. diameter

Aluminium sector cable

Tool data

Depth / Width / Height

Weight

Note**Ordering data****Version****KT 80**

630 mm²

630 mm² / 1260 kcmil

3 x 240 SM

1000 mm² / 2000 kcmil

4 x 240 SE

55 / 675 / 175 mm

3240 g

Note

Type	Qty.	Order No.
KT 80	1	9202080000

The dimensions of the cable cutter refer to the delivery condition, i.e. the point of the hinged blade parallel to the fixed blade.

Accessories**Note**

Type	Qty.	Order No.
ERME KT 80	1	9204290000

Spare pivoting cutter