

**KT MINI****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools (KT 8 to KT 22) also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

**General ordering data**

Version	Cutting tools
Order No.	<a href="#">2876460000</a>
Type	KT MINI
GTIN (EAN)	4064675664024
Qty.	1 pc(s).

## KT MINI

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Depth	9.5 mm	Depth (inches)	0.374 inch
Height	120 mm	Height (inches)	4.724 inch
Width	42 mm	Width (inches)	1.654 inch
Net weight	91 g		

### Cutting tools

Copper cable - flexible, max.	16 mm <sup>2</sup>	Copper cable - flexible, max. (AWG)	6 AWG
Copper cable - solid, max.	35 mm <sup>2</sup>	Copper cable - solid, max. (AWG)	2 AWG
Copper cable - stranded, max.	25 mm <sup>2</sup>	Copper cable - stranded, max. (AWG)	4 AWG
Copper cable, max. diameter	7 mm	Single-core aluminium cable, max.(mm <sup>2</sup> )	35 mm <sup>2</sup>
Stranded aluminium cable, max (mm <sup>2</sup> )	25 mm <sup>2</sup>	Stranded aluminium cable, max. (AWG)	4 AWG
Stranded aluminium cable, max. diameter	7 mm		

### Classifications

ETIM 6.0	EC000142	ETIM 7.0	EC000142
ETIM 8.0	EC000142	ETIM 9.0	EC000142
ECLASS 9.0	21-04-47-01	ECLASS 9.1	21-04-37-06
ECLASS 10.0	21-04-47-01	ECLASS 11.0	21-04-47-01
ECLASS 12.0	21-04-47-01	ECLASS 13.0	21-04-47-01
ECLASS 14.0	21-04-47-01		

### Environmental Product Compliance

RoHS Compliance Status	Not affected
REACH SVHC	Lead 7439-92-1
SCIP	cf06c250-ed1e-4a45-9c1b-c5c8cbf13bf0

### Downloads

Catalogues	<a href="#">Catalogues in PDF-format</a>
------------	--