



PROFESSIONAL



EN 131

- Bij gebruik in A-stand (dubbel gezet), de ladder bestijgen via het smalle deel.
- Maximale draagkracht: 150 kg
- Afstand tussen 2 sporten: 25 cm
- 10 jaar garantie



Omvormbaar

Schuifladder/omvormbaar

3 x 6	1,75 m	3,50 m	77 cm	60	12,5 kg
3 x 7	2,00 m	4,25 m	87 cm	60	14,0 kg
3 x 8	2,25 m	4,75 m	87 cm	60	16,5 kg
3 x 9	2,50 m	5,50 m	99 cm	65	18,5 kg
3 x 10	2,75 m	6,25 m	99 cm	65	20,5 kg
3 x 12*	3,40 m	8,15 m	123 cm	70	26,0 kg
3 x 14*	3,90 m	9,15 m	123 cm	72	34,0 kg

Ook verkrijgbaar met rechte voet en stabiliteitsbalk (STAB - zie tabel op pag 15).

* Model 3 x 12 en 3 x 14 standaard uitgerust met gevelrollen en verbredingsvoeten.

Schuifladder/niet-omvormbaar

3 x 16RB	4,40 m	9,70 m	124 cm	80	38,0 kg
3 x 18RB	4,90 m	11,65 m	124 cm	80	45,0 kg

Standaard uitgerust met gevelrollen en stabiliteitsbalk (STAB - zie tabel op pag 15).



Gevelrollen

